

Sparepart documentation



SW 10x6 BASIC

Prod. No.: 360659

Product details:

Serving trolleys
Made of corrosion-resistant stainless steel
Dimensions of shelves: 1000 x 600mm
max. load per shelf:80 kg
Illustration similar

Spareparts





Image	Code	Name	Quantity in device
	<u>136020</u>	PLATE, NOISE-SUPPR. 500X190X1,9 (valid from 01/22/2001)	1.0 Each
	<u>373304</u>	Wall guard D100 RAL 7043 (valid from 11/21/2003)	4.0 Each
	<u>373984</u>	Cast. whl. 125 lock., pegs, RD22.5, galv (valid from 10/17/2011)	2.0 Each
	<u>373985</u>	Cast. whl. 125, pegs, RD22.5, galv. (valid from 10/17/2011)	2.0 Each
	<u>70609</u>	SCREW, CYL. HEX. M6 X 16 DIN 912 1.4301 (valid from 10/17/2011)	4.0 Each
	<u>382558</u>	Cast. wl 125 lck., DIN pegs, PA, antist. (valid from 03/01/2018)	2.0 Each
	<u>386513</u>	Swivel castor 125 lock,DIN-Zpf,PA, anti. (valid from 04/01/2022)	2.0 Each







Image	Code	Name	Quantity in device
	<u>382555</u>	Fixed wheel 125 DIN pegs, PA (gary) (valid from 03/01/2018)	2.0 Each
	<u>360281</u>	Adapter sleeve D22.5x62 (valid from 10/17/2011)	4.0 Each
	<u>386500</u>	Swivel castor 125, DIN-Pin, (gray) (valid from 08/02/2022)	2.0 Each
	<u>386499</u>	Swivel castor 125 lock., DIN-Pin (gray) (valid from 08/02/2022)	2.0 Each
	<u>145125</u>	WHEEL, CAST.- 180RD LUFT R05 (valid from 01/22/2001)	4.0 Each
	<u>146944</u>	CAST. WHL. 125 G 10x15 CNS (valid from 05/17/2001)	2.0 Each
	<u>146945</u>	CAST. WHL 125 TOT LOCK CNS TPR GL TD. 10 (valid from 05/17/2001)	2.0 Each
	<u>144142</u>	Round pin d=22, L=45 galvanised (valid from 05/17/2001)	4.0 Each
	<u>386503</u>	Swivel cast. 125 lock.,DIN-Pin air iden. (valid from 06/10/2022)	2.0 Each

Image	Code	Name	Quantity in device
	<u>386506</u>	Swivel castor 125,DIN-Zpf,PA air iden. (valid from 06/10/2022)	2.0 Each
	<u>382721</u>	Castor wheel ZPF FS Ø 125 galv. air id. (valid from 07/16/2021)	2.0 Each
	<u>382722</u>	Castor wheel ZPF Ø 125 galv. air id. (valid from 07/16/2021)	2.0 Each