


Sparepart documentation



BME-I 1/1

Prod. No.: 566262

Product details:

Build-in bain-marie with fastening elements for installation in Resopal top surfaces etc. Seamlessly deep-drawn with all-round slosh
with drain connection piece
with insulation housing, heating mode: wet and dry, for GN 1/1 or its subdivisions
Temperature control from +30 °C to +110 °C
Rotary switch for thermostat with indicator lamp

Spareparts
















Image	Code	Name	Quantity in device
	<u>367982</u>	Heating well, complete, 700 W (valid from 09/05/1997)	1.0 Each
	<u>105020</u>	PIPE HEATER 20.21719.000 700W 230V (valid from 09/05/1997)	1.0 Each
	<u>294096</u>	SENSOR MOUNTING F.GN (valid from 05/18/2006)	1.0 Each
	<u>257793</u>	Mounting plate (valid from 09/05/1997)	1.0 Each
	<u>145288</u>	MATTE,STEINWOLL- 1000X625x20 ALUF.1SEIT. (valid from 04/27/1998)	0.374 Square meter
	<u>105127</u>	Capillary tube controller 55.13624.01 (valid from 09/05/1997)	1.0 Each
	<u>105188</u>	LAMP,SIGNAL- SGF 14/6 E 230V GREEN (valid from 09/05/1997)	1.0 Each
	<u>105429</u>	terminal block Wieland KL 24/3 SL (valid from 09/05/1997)	1.0 Each
	<u>267063</u>	Seal for controller + switch (valid from 09/05/1997)	1.0 Each

Image	Code	Name	Quantity in device
	<u>105135</u>	TOGGLE,SWITCH- 110 DEG 247 (valid from 09/05/1997)	1.0 Each
	<u>105301</u>	HOSE,INSULAT. TYPE 01472 8/9 BLACK (valid from 09/05/1997)	0.6 Meter
	<u>262354</u>	Pipe drain G 1/2" L=19mm (valid from 01/07/1998)	1.0 Each
	<u>146648</u>	Teflon seal 36 x 27 x 2 (valid from 01/07/1998)	1.0 Each
	<u>83138</u>	WASHER,BACKING A 21,0 DIN 125 1.4301 (valid from 09/05/1997)	1.0 Each
	<u>144544</u>	RING,SEAL-KLINGERIT 1X26X21 1/2" (valid from 01/07/1998)	1.0 Each
	<u>376256</u>	Extension 1/2"x60 VI 1513 (valid from 01/07/1998)	1.0 Each
	<u>221393</u>	Clamping el.2 rests s/s sinks 28-40exp. (valid from 01/07/1998)	6.0 Each