

Sparepart documentation



BASIC LINE W-3

Prod. No.: 381877

Product details:

Hot buffet 3 x GN 1/1
Stainless-steel top surface with three seamlessly welded-in bain-maries with central safety drain valve.
Bain-maries can be individually heated wet or dry.
Capacity: 3 x GN 1/1, max. depth 200 mm
Basin temperature range: +30 °C to +95 °C
Exterior dimensions (without options or accessories):
W x D x H (mm) 1255 x 690 x 900 / 1305 (with bridge attachment)

Spareparts


Image	Code	Name	Quantity in device
	367982	Heating well, complete, 700 W (valid from 08/28/2017)	3.0 Each
	105020	PIPE HEATER 20.21719.000 700W 230V (valid from 08/28/2017)	1.0 Each
	294096	SENSOR MOUNTING F.GN (valid from 08/28/2017)	3.0 Each
	384629	Drain 3x1/1 BasicLine (valid from 02/04/2020)	1.0 Each
	146649	Washer 27 x 36 x 1 DIN 988 A 2 (valid from 08/28/2017)	3.0 Each
	146648	Teflon seal 36 x 27 x 2 (valid from 08/28/2017)	3.0 Each
	262353	PIPE, DRAIN- (valid from 08/28/2017)	3.0 Each
	107512	LED spot IPLine LCH-023_3000K (WW) (valid from 08/28/2017)	3.0 Each




Image	Code	Name	Quantity in device
	<u>146667</u>	COLLAR (valid from 01/08/2018)	1.0 Each
	<u>381746</u>	Mica plate for heat radiators (valid from 08/28/2017)	3.0 Each
	<u>381747</u>	Mica plate 237x36x0,5 (valid from 08/28/2017)	6.0 Each
	<u>107552</u>	Infrared radiator HTS/2 230V / 200W (valid from 10/28/2019)	3.0 Each
	<u>105301</u>	HOSE,INSULAT. TYPE 01472 8/9 BLACK (valid from 11/06/2017)	1.26 Meter
	<u>107755</u>	Socket clamp BM 9517 (valid from 08/28/2017)	3.0 Each
	<u>106184</u>	Warning sign hot surface (valid from 08/28/2017)	1.0 Each
	<u>382160</u>	Glas pillar - without heat radiator (valid from 08/28/2017)	1.0 Each
	<u>381871</u>	Glas pillar Standard (valid from 08/28/2017)	2.0 Each
	<u>384707</u>	Washer rubber (valid from 08/28/2017)	1.0 Each




Image	Code	Name	Quantity in device
	381415	Sneeze guard holder (valid from 08/28/2017)	2.0 Each
	134267	Glass support Highline with mounting (valid from 02/05/2025)	1.0 Each
	384708	Rubber washer (valid from 08/28/2017)	1.0 Each
	71323	Screw M5x10 DIN551 (valid from 08/28/2017)	1.0 Each
	144885	PLUG-LAMINATE- 25RD BLK. (valid from 09/19/2018)	6.0 Each
	369011	Tube tray slide 3x1/1 (valid from 08/28/2017)	1.0 Each
	385974	Mini fastening 822-4-C-NI (valid from 02/05/2021)	1.0 Each
	378652	Tray slide 3x1/1 (valid from 08/28/2017)	1.0 Each
	378645	Plate slide 3x1/1 (valid from 08/28/2017)	1.0 Each

Image	Code	Name	Quantity in device
	369402	Tube tray slide face side (valid from 08/28/2017)	1.0 Each
	378640	Stabling shelf face side cpl. (valid from 08/28/2017)	1.0 Each
	379760	Tray shelf face side (valid from 08/28/2017)	1.0 Each
	105029	Tubular heater 250W 20.21843 230V (valid from 08/28/2017)	2.0 Each
	105899	Thermostat capillar 55.18019.130 35-85°C (valid from 08/28/2017)	1.0 Each
	267063	Seal for controller + switch (valid from 08/28/2017)	1.0 Each
	292846	Toggle dia. 42 with labelling (valid from 08/28/2017)	1.0 Each
	107035	Mounting thermometer digital display (valid from 08/28/2017)	1.0 Each
	106868	Power switch bipolar 16A B4MASK-series (valid from 08/28/2017)	1.0 Each
	376806	Shell type handle RAL 7043 (valid from 08/28/2017)	1.0 Each
	246471	Washer (valid from 08/28/2017)	4.0 Each
	71357	Slotted headless screw M4x20 A1 ISO 2342 (valid from 08/28/2017)	2.0 Each





Image	Code	Name	Quantity in device
	<u>381830</u>	Hinge bottom part (valid from 08/28/2017)	2.0 Each
	<u>144345</u>	Ball catch IDEAL size III brass 70x13R (valid from 08/28/2017)	2.0 Each
	<u>298579</u>	Spacer 6 mm (valid from 08/28/2017)	4.0 Each
	<u>146506</u>	Glass wool 540x420x20 (valid from 08/28/2017)	2.0 Each
	<u>279539</u>	Distance sheet for ball catch 2 mm (valid from 08/28/2017)	2.0 Each
	<u>380810</u>	Bottom 3x1/1 cpl. (valid from 08/28/2017)	1.0 Each
	<u>381205</u>	Hinge cpl. Bottom left (valid from 08/28/2017)	1.0 Each
	<u>381204</u>	Hinge cpl. Bottom right (valid from 08/28/2017)	1.0 Each
	<u>382844</u>	Counter part magnet (valid from 01/16/2020)	2.0 Each
	<u>381373</u>	Magnetic snapper 245.67.310 (valid from 08/28/2017)	2.0 Each
	<u>381724</u>	Pot magnet with threaded pin GTN-10 (valid from 02/26/2020)	4.0 Each




Image	Code	Name	Quantity in device
	369185	DOUBLE STR. CASTOR75 lock.boa.galv. steel (valid from 08/28/2017)	2.0 Each
	369186	DOUBLE STR. CASTOR 75 board galv. steel (valid from 08/28/2017)	2.0 Each
	380419	Adjustable foot cpl. (valid from 08/28/2017)	4.0 Each
	145056	WHEEL, CASTER-2470 PJO 125 P60 CNS (valid from 08/28/2017)	2.0 Each
	145057	WHEEL, CASTER- 2477 PJO 125 P60 CNS (valid from 08/28/2017)	2.0 Each
	384285	Fixing plate komplet (valid from 08/28/2017)	4.0 Each
	381001	Balancing plate (valid from 08/28/2017)	4.0 Each
	146680	EXPAND. NUT 72.30.459 F. SHEET SCRW. 4.2 (valid from 08/28/2017)	4.0 Each
	383836	Ball valve 1/2" (valid from 02/27/2019)	1.0 Each
	383869	Extension 1/2"x25 VI 1513 MS (valid from 02/28/2019)	1.0 Each


Image	Code	Name	Quantity in device
	<u>106304</u>	Cable gland M20x1.5 black (valid from 08/28/2017)	1.0 Each
	<u>106311</u>	Hexagon nut M20x1.5 (plastic) (valid from 08/28/2017)	1.0 Each
	<u>105494</u>	terminal block Wieland KL 24/5 SL (valid from 08/28/2017)	1.0 Each
	<u>106380</u>	Capillary tube controller 27-106°C (valid from 08/28/2017)	3.0 Each
	<u>105902</u>	CABLE H07RN-F 3X1,5QMM3M LONG (valid from 08/28/2017)	1.0 Each
	<u>107658</u>	Spiral cable Europa 3x1,5qmm_long (valid from 12/10/2021)	1.0 Each
	<u>105489</u>	CABLE-RUBBER- H07 RN-F 3X1,5 QMM BLACK (valid from 08/28/2017)	3.0 Meter
	<u>105876</u>	PLUG, ENGLAND 351363/A 13 AMP 250 V (valid from 08/28/2017)	1.0 Each
	<u>106850</u>	Plug 230V / 16A CH type 23 (valid from 08/28/2017)	1.0 Each
	<u>107256</u>	CABLE 230V, H07RN-F 3M LONG CH (valid from 08/28/2017)	1.0 Each
	<u>106702</u>	Connecting cable H07RN-F 5x1,5mm²/4, 5m (valid from 08/28/2017)	1.0 Each
	<u>107659</u>	Spiral cable open ends 5x1,5 qmm long (valid from 12/10/2021)	1.0 Each

Image	Code	Name	Quantity in device
	<u>100085</u>	CABLE, RUBBER-SHEATHED. NMH 5X1, 5 QMM (valid from 08/28/2017)	3.0 Meter
	<u>107776</u>	Plug KALTHOFF SEV IP55, Typ15, CH (valid from 01/25/2023)	1.0 Each
	<u>104094</u>	PLUG-CEE 5x16A (valid from 12/10/2021)	1.0 Each
	<u>107809</u>	Plug 400V/16A CH Typ 25 (valid from 08/28/2017)	1.0 Each
	<u>106891</u>	seal for ABL electrical outlets (valid from 08/09/2021)	1.0 Each
	<u>107554</u>	Socket Typ 1661060 (valid from 08/28/2017)	2.0 Each
	<u>107716</u>	Socket outlet protective contact-black (valid from 05/03/2022)	1.0 Each
	<u>106802</u>	Build-in socket CH 10A T13 (valid from 08/28/2017)	2.0 Each
	<u>107715</u>	Protective-socket Swiss-Standard T13 bla (valid from 05/03/2022)	1.0 Each
	<u>107701</u>	Build-in socket CH typ 23 seid. (valid from 04/12/2022)	2.0 Each
	<u>106803</u>	Build-in socket British standard (valid from 08/28/2017)	2.0 Each

Image	Code	Name	Quantity in device
	<u>106822</u>	Safety socket Denmark <i>(valid from 08/28/2017)</i>	2.0 Each
	<u>106737</u>	Build-in socket with pin <i>(valid from 08/28/2017)</i>	2.0 Each
	<u>107514</u>	LED converter univer. 20W BI; 350-700mA <i>(valid from 08/28/2017)</i>	1.0 Each
	<u>107524</u>	Axial AC FAN 80mm 230V SF23080A <i>(valid from 08/28/2017)</i>	1.0 Each