

Sparepart documentation



BASIC LINE UK-3 Kids

Prod. No.: 381901

Product details:

Cold buffet with active convection cooling 3 x GN 1/1 with a low height
 Module serving height: 750 mm
 Stainless-steel top surface with seamlessly welded-in, convection-cooled 3/1 GN well with manually emptied condensation-water catch tray.
 Completely encapsulated refrigeration unit in underframe, ready to plug in.
 Temperature controller on the operator-side panel.
 Capacity: 3 x GN 1/1, max. depth: 200 mm
 Temperature range: +2 °C to +15 °C
 Exterior dimensions (without options or accessories):
 W x D x H (mm)
 1255 x 690 x 750 / 1155 (with bridge attachment)

Spareparts


Image	Code	Name	Quantity in device
	146698	Plug GPN 910/3759 (valid from 10/26/2017)	2.0 Each
	149764	Evaporator 3x1/1 R290 Cathaphorese Coat (valid from 03/11/2022)	1.0 Each
	358334	Evaporator 3x1/1 (valid from 09/18/2017)	1.0 Each
	358978	Protective grid fan (valid from 09/18/2017)	1.0 Each
	149201	Axial fan 8556 VWU 230V 50/60Hz 12W (valid from 09/18/2017)	1.0 Each
	107513	LED spot IPLine LCH-023_4200K (NW) (valid from 09/18/2017)	3.0 Each
	381871	Glas pillar Standard (valid from 02/19/2025)	1.0 Each



Image	Code	Name	Quantity in device
	<u>382160</u>	Glas pillar - without heat radiator (valid from 02/19/2025)	1.0 Each
	<u>381415</u>	Sneeze guard holder (valid from 09/18/2017)	2.0 Each
	<u>134267</u>	Glass support Highline with mounting (valid from 02/05/2025)	1.0 Each
	<u>384708</u>	Rubber washer (valid from 09/18/2017)	1.0 Each
	<u>71323</u>	Screw M5x10 DIN551 (valid from 05/11/2020)	2.0 Each
	<u>144885</u>	PLUG-LAMINATE- 25RD BLK. (valid from 09/19/2018)	6.0 Each
	<u>369011</u>	Tube tray slide 3x1/1 (valid from 09/18/2017)	1.0 Each
	<u>385974</u>	Mini fastening 822-4-C-NI (valid from 02/05/2021)	1.0 Each




Image	Code	Name	Quantity in device
	<u>378652</u>	Tray slide 3x1/1 (valid from 09/18/2017)	1.0 Each
	<u>378645</u>	Plate slide 3x1/1 (valid from 09/18/2017)	1.0 Each
	<u>369402</u>	Tube tray slide face side (valid from 09/18/2017)	1.0 Each
	<u>378640</u>	Stabling shelf face side cpl. (valid from 09/18/2017)	1.0 Each
	<u>379760</u>	Tray shelf face side (valid from 09/18/2017)	1.0 Each
	<u>381724</u>	Pot magnet with threaded pin GTN-10 (valid from 09/28/2017)	4.0 Each
	<u>246471</u>	Washer (valid from 11/28/2018)	2.0 Each
	<u>381205</u>	Hinge cpl. Bottom left (valid from 09/18/2017)	1.0 Each
	<u>381373</u>	Magnetic snapper 245.67.310 (valid from 09/18/2017)	1.0 Each
	<u>369185</u>	DOUBLE STR. CASTOR75 lock.boa.galv. steel (valid from 09/18/2017)	2.0 Each
	<u>369186</u>	DOUBLE STR. CASTOR 75 board galv. steel (valid from 09/18/2017)	2.0 Each
	<u>380419</u>	Adjustable foot cpl. (valid from 09/18/2017)	4.0 Each



Image	Code	Name	Quantity in device
	<u>145056</u>	WHEEL, CASTER-2470 PJO 125 P60 CNS (valid from 09/18/2017)	2.0 Each
	<u>145057</u>	WHEEL, CASTER- 2477 PJO 125 P60 CNS (valid from 09/18/2017)	2.0 Each
	<u>384285</u>	Fixing plate komplet (valid from 09/18/2017)	4.0 Each
	<u>381001</u>	Balancing plate (valid from 09/18/2017)	4.0 Each
	<u>146680</u>	EXPAND. NUT 72.30.459 F. SHEET SCRW. 4.2 (valid from 09/18/2017)	4.0 Each
	<u>293685</u>	Insert grate (valid from 09/19/2017)	3.0 Each
	<u>372357</u>	Air ventilation sheet 3x1/1 (valid from 09/19/2017)	2.0 Each
	<u>106304</u>	Cable gland M20x1.5 black (valid from 09/18/2017)	1.0 Each
	<u>106311</u>	Hexagon nut M20x1.5 (plastic) (valid from 09/18/2017)	1.0 Each
	<u>105494</u>	terminal block Wieland KL 24/5 SL (valid from 09/18/2017)	1.0 Each
	<u>106868</u>	Power switch bipolar 16A B4MASK-series (valid from 09/18/2017)	1.0 Each

Image	Code	Name	Quantity in device
	<u>107662</u>	Power switch bipolar 16A B4MASK-Ser. ATEX (valid from 03/11/2022)	1.0 Each
	<u>134192</u>	Digital con. BASIC-LINE UK-3 / UK-4 (valid from 03/11/2022)	1.0 Each
	<u>106926</u>	Sensor SN7PK150 NTC, 1.5m (valid from 09/18/2017)	1.0 Each
	<u>149754</u>	Filter drier DTG-b05 061-901 (valid from 09/20/2021)	1.0 Each
	<u>149758</u>	filter drier Danfoss DML 1.52s 023Z8254 (valid from 03/11/2022)	1.0 Each
	<u>149630</u>	Ex. valve Danfoss TUA f. R134a < 12.2021 (valid from 09/18/2017)	1.0 Each
	<u>370254</u>	Nozzle 3 for TUA-valve 068U1033 (valid from 09/18/2017)	1.0 Each
	<u>105789</u>	RUBBER SEAL GU 000000 (valid from 09/18/2017)	1.0 Each
	<u>105902</u>	CABLE H07RN-F 3X1,5QMM3M LONG (valid from 09/18/2017)	1.0 Each
	<u>107658</u>	Spiral cable Europa 3x1,5qmm_long (valid from 12/10/2021)	1.0 Each
	<u>105489</u>	CABLE-RUBBER- HO7 RN-F 3X1,5 QMM BLACK (valid from 09/18/2017)	3.0 Meter
	<u>105876</u>	PLUG, ENGLAND 351363/A 13 AMP 250 V (valid from 09/18/2017)	1.0 Each

Image	Code	Name	Quantity in device
	<u>106850</u>	Plug 230V / 16A CH type 23 (valid from 09/18/2017)	1.0 Each
	<u>107256</u>	CABLE 230V, H07RN-F 3M LONG CH (valid from 09/18/2017)	1.0 Each
	<u>106702</u>	Connecting cable H07RN-F 5x1,5mm²/4, 5m (valid from 09/18/2017)	1.0 Each
	<u>107659</u>	Spiral cable open ends 5x1,5 qmm long (valid from 12/10/2021)	1.0 Each
	<u>100085</u>	CABLE, RUBBER-SHEATHED. NMH 5X1, 5 QMM (valid from 09/18/2017)	3.0 Meter
	<u>107776</u>	Plug KALTHOFF SEV IP55, Typ15, CH (valid from 01/25/2023)	1.0 Each
	<u>104094</u>	PLUG-CEE 5x16A (valid from 12/10/2021)	1.0 Each
	<u>107809</u>	Plug 400V/16A CH Typ 25 (valid from 09/18/2017)	1.0 Each
	<u>106891</u>	seal for ABL electrical outlets (valid from 08/09/2021)	1.0 Each
	<u>107554</u>	Socket Typ 1661060 (valid from 09/18/2017)	2.0 Each
	<u>107716</u>	Socket outlet protective contact-black (valid from 05/03/2022)	1.0 Each
	<u>106802</u>	Build-in socket CH 10A T13 (valid from 09/18/2017)	2.0 Each

Image	Code	Name	Quantity in device
	<u>107715</u>	Protective-socket Swiss-Standard T13 bla (valid from 05/03/2022)	1.0 Each
	<u>107701</u>	Build-in socket CH typ 23 seid. (valid from 04/12/2022)	2.0 Each
	<u>106803</u>	Build-in socket British standard (valid from 09/18/2017)	2.0 Each
	<u>106822</u>	Safety socket Denmark (valid from 09/18/2017)	2.0 Each
	<u>106737</u>	Build-in socket with pin (valid from 09/18/2017)	2.0 Each
	<u>107514</u>	LED converter univer. 20W BI; 350-700mA (valid from 09/18/2017)	1.0 Each