

Sparepart documentation



UNI-H 59/29

Prod. No.: 572195

Product details:

Universal dispenser,
heatable (convection)
+30 °C to +110 °C,
closed model
Made of corrosion-resistant stainless steel
Capacity: dependent on type of dishes
Stacking height: with hooded cover: 680 mm without hooded cover: 540mm
basic model
362749

PI

Spareparts

Image	Code	Name	Quantity in device
	146302	Tension spring 20GR (valid from 09/23/2002)	8.0 Each
	364814	Tray cpl. 59/29 perforated (valid from 09/23/2002)	1.0 Each
	146285	BEARING, STEEL- (valid from 09/23/2002)	4.0 Each
	379653	Guidance rod D16-780 (valid from 03/07/2014)	6.0 Each
	385096	Seal 9x5,5 black (valid from 02/05/2020)	1.0 Meter
	105913	Radial fan R2A 150-AC01-21 (valid from 09/23/2002)	1.0 Each
	105708	Tubular heater 1800W Nr. 20.28907.000 (valid from 09/23/2002)	1.0 Each
	369654	Plug holder universal (valid from 03/17/2008)	1.0 Each

Image	Code	Name	Quantity in device
	<u>117766</u>	plastic cover ring for plug holder (valid from 10/02/2008)	1.0 Each
	<u>107650</u>	Spiral cable Europe 3x1,5 qmm WG BL-650 (valid from 03/03/2021)	1.0 Each
	<u>106304</u>	Cable gland M20x1.5 black (valid from 09/23/2002)	1.0 Each
	<u>106311</u>	Hexagon nut M20x1.5 (plastic) (valid from 09/23/2002)	1.0 Each
	<u>106868</u>	Power switch bipolar 16A B4MASK-series (valid from 03/07/2008)	1.0 Each
	<u>146902</u>	FIXING COLLAR (valid from 09/23/2002)	1.0 Each
	<u>106344</u>	Temp. guard 135°C KO 340-135-03-A (valid from 09/23/2002)	1.0 Each
	<u>105900</u>	Thermostat capillar 55.18022.040 35-130° (valid from 09/23/2002)	1.0 Each
	<u>267063</u>	Seal for controller + switch (valid from 09/23/2002)	1.0 Each
	<u>292846</u>	Toggle dia. 42 with labelling (valid from 09/23/2002)	1.0 Each
	<u>297578</u>	TEMP.-LIMITER 150°C KB 344-150-05-A (valid from 09/23/2002)	1.0 Each
	<u>106348</u>	Cable harness, CHV/2SHV/UNI-H (valid from 09/23/2002)	1.0 Each


Image	Code	Name	Quantity in device
	<u>386502</u>	Swivel castor 125, DIN-PL, (gray) (valid from 08/24/2022)	2.0 Each
	<u>386501</u>	Swivel castor 125 lock., DIN-PL (gray) (valid from 08/24/2022)	2.0 Each
	<u>146904</u>	Cover hood UNI 59/29 (valid from 09/23/2002)	1.0 Each
	<u>376812</u>	Corner guard closed RAL7043 (valid from 03/18/2014)	4.0 Each
	<u>376371</u>	Plug corner guard RAL 7043 (valid from 03/18/2014)	16.0 Each
	<u>146680</u>	EXPAND. NUT 72.30.459 F. SHEET SCRW. 4.2 (valid from 09/23/2002)	12.0 Each
	<u>363257</u>	Pipe 32x1,5x 412 Fixl. 1.4301 GSL 220 K (valid from 09/23/2002)	1.0 Each
	<u>376808</u>	Push-handle holder right RAL7043 (valid from 03/17/2014)	1.0 Each
	<u>376809</u>	Push-handle holder left RAL7043 (valid from 03/17/2014)	1.0 Each
	<u>81320</u>	Tapping screw ISO7051-ST4,2x19 (valid from 09/23/2002)	4.0 Each
	<u>376810</u>	Cover for right. push hand., grey RAL7043 (valid from 03/17/2014)	1.0 Each

Image	Code	Name	Quantity in device
	<u>376811</u>	Cover for left push hand., grey RAL7043 (valid from 03/17/2014)	1.0 Each
	<u>358964</u>	Label-no plastic (valid from 09/23/2002)	1.0 Each
	<u>106184</u>	Warning sign hot surface (valid from 09/23/2002)	1.0 Each
	<u>298743</u>	PLUG 30 ROUND PE BLACK (valid from 09/23/2002)	2.0 Each