

# Sparepart documentation



## [CE-UK 53/53](#)


**Prod. No.:** 572431

### **Product details:**

Basket dispenser, cooled  
Made of corrosion-resistant stainless steel  
Basket dimensions: 500 x 500/525 x 525 mm  
Capacity: 5 baskets with 115 mm or 8 baskets of 75 mm height  
Stacking height: with hooded cover: 680 mm without hooded cover: 54  
basic model 364573

## Spareparts

| Image | Code                   | Name                                                               | Quantity in device |
|-------|------------------------|--------------------------------------------------------------------|--------------------|
|       | <a href="#">144345</a> | Ball catch IDEAL size III brass 70x13R<br>(valid from 02/16/2004)  | 2.0 Each           |
|       | <a href="#">149284</a> | PROFILE, INSERTION, GREY, NO. SH 6554<br>(valid from 02/16/2004)   | 0.656 Meter        |
|       | <a href="#">376806</a> | Shell type handle RAL 7043<br>(valid from 02/16/2004)              | 2.0 Each           |
|       | <a href="#">364595</a> | Sealing frame cooled basket dispenser<br>(valid from 02/16/2004)   | 1.0 Each           |
|       | <a href="#">376812</a> | Corner guard closed RAL7043<br>(valid from 03/18/2014)             | 4.0 Each           |
|       | <a href="#">376371</a> | Plug corner guard RAL 7043<br>(valid from 03/18/2014)              | 16.0 Each          |
|       | <a href="#">146680</a> | EXPAND. NUT 72.30.459 F. SHEET SCR. 4.2<br>(valid from 02/16/2004) | 12.0 Each          |
|       | <a href="#">146302</a> | Tension spring 20GR<br>(valid from 02/16/2004)                     | 12.0 Each          |

| Image                                                                               | Code                          | Name                                                                | Quantity in device |
|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------|--------------------|
|    | <a href="#"><u>296813</u></a> | Cover hood square 813<br>(valid from 02/16/2004)                    | 1.0 Each           |
|    | <a href="#"><u>146285</u></a> | BEARING, STEEL-<br>(valid from 02/16/2004)                          | 4.0 Each           |
|    | <a href="#"><u>362755</u></a> | Tube, 32x1.5x642, fixed L, 1.4301<br>K<br>(valid from 02/16/2004)   | 1.0 Each           |
|    | <a href="#"><u>376808</u></a> | Push-handle holder right RAL7043<br>(valid from 03/17/2014)         | 1.0 Each           |
|    | <a href="#"><u>376809</u></a> | Push-handle holder left RAL7043<br>(valid from 03/17/2014)          | 1.0 Each           |
|                                                                                     | <a href="#"><u>81320</u></a>  | Tapping screw ISO7051-ST4, 2x19<br>(valid from 02/16/2004)          | 4.0 Each           |
|  | <a href="#"><u>376810</u></a> | Cover for right push hand., grey RAL7043<br>(valid from 03/17/2014) | 1.0 Each           |
|  | <a href="#"><u>376811</u></a> | Cover for left push hand., grey RAL7043<br>(valid from 03/17/2014)  | 1.0 Each           |
|  | <a href="#"><u>386501</u></a> | Swivel castor 125 lock., DIN-PL (gray)<br>(valid from 08/24/2022)   | 2.0 Each           |
|  | <a href="#"><u>382548</u></a> | Fixed wheel 125 DIN-PL, PA (gray)<br>(valid from 03/01/2018)        | 2.0 Each           |
|  | <a href="#"><u>149577</u></a> | Evaporator Polar SKW382 Lüfter IP54<br>(valid from 02/16/2004)      | 1.0 Each           |
|  | <a href="#"><u>106868</u></a> | Power switch bipolar 16A B4MASK-series<br>(valid from 03/07/2008)   | 1.0 Each           |

| Image                                                                               | Code                          | Name                                                                | Quantity in device |
|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------|--------------------|
|    | <a href="#"><u>105848</u></a> | PTC sensor SN6P0150<br>(valid from 02/16/2004)                      | 1.0 Each           |
|    | <a href="#"><u>134184</u></a> | Digital controller CE-UK<br>(valid from 11/17/2022)                 | 1.0 Each           |
|    | <a href="#"><u>149630</u></a> | Ex. valve Danfoss TUA f. R134a < 12.2021<br>(valid from 09/25/2008) | 1.0 Each           |
|    | <a href="#"><u>370252</u></a> | Nozzle 1 f.TUA-valve 068U1031<br>(valid from 09/25/2008)            | 1.0 Each           |
|    | <a href="#"><u>149754</u></a> | Filter drier DTG-b05 061-901<br>(valid from 09/20/2021)             | 1.0 Each           |
|   | <a href="#"><u>105429</u></a> | terminal block Wieland KL 24/3 SL<br>(valid from 02/16/2004)        | 1.0 Each           |
|  | <a href="#"><u>105494</u></a> | terminal block Wieland KL 24/5 SL<br>(valid from 02/16/2004)        | 1.0 Each           |
|  | <a href="#"><u>107649</u></a> | Spiral cable Europe 3x1,5 qmmst WG<br>(valid from 03/03/2021)       | 1.0 Each           |
|  | <a href="#"><u>106304</u></a> | Cable gland M20x1.5 black<br>(valid from 02/16/2004)                | 1.0 Each           |
|  | <a href="#"><u>106311</u></a> | Hexagon nut M20x1.5 (plastic)<br>(valid from 02/16/2004)            | 1.0 Each           |
|  | <a href="#"><u>105316</u></a> | CABLE-NYMHY-J 3X1,0 BLACK<br>(valid from 02/16/2004)                | 2.0 Meter          |
|  | <a href="#"><u>369654</u></a> | Plug holder universal<br>(valid from 03/17/2008)                    | 1.0 Each           |

| Image                                                                             | Code                   | Name                                                                 | Quantity in device |
|-----------------------------------------------------------------------------------|------------------------|----------------------------------------------------------------------|--------------------|
|  | <a href="#">117766</a> | plastic cover ring for plug holder<br><i>(valid from 10/02/2008)</i> | 1.0 Each           |