

Sparepart documentation



STW 2

Prod. No.: 572496

Product details:

Food transport trolleys
Made of corrosion-resistant stainless steel
2 compartments,
temperature range: +30 °C to +85 °C
Compartments: 2 compartments, heatable, with 9 pairs of support ledges
each for GN 1/1, spacing: 57.5 mm
basic model 362575
Illustration similar (572159 STW 2)

Spareparts


Image	Code	Name	Quantity in device
	362192	Door kpl. left (valid from 09/05/2016)	1.0 Each
	376806	Shell type handle RAL 7043 (valid from 09/05/2016)	1.0 Each
	144345	Ball catch IDEAL size III brass 70x13R (valid from 09/05/2016)	1.0 Each
	279539	Distance sheet for ball catch 2 mm (valid from 09/05/2016)	1.0 Each
	83031	washer A 8.4 DIN 125 brass (valid from 09/05/2016)	1.0 Each
	146516	NUT, ROUNDHEAD- M5 (valid from 09/05/2016)	1.0 Each
	70914	Allen screw ISO 7380 M5x8 A2 m. Fl. (valid from 09/05/2016)	1.0 Each
	362191	Door kpl. right (valid from 09/05/2016)	1.0 Each
	276953	HEATING 250W F. HEATED CABINET (valid from 09/05/2016)	4.0 Each




Image	Code	Name	Quantity in device
	<u>105029</u>	Tubular heater 250W 20.21843 230V (valid from 09/05/2016)	1.0 Each
	<u>146902</u>	FIXING COLLAR (valid from 09/05/2016)	2.0 Each
	<u>386501</u>	Swivel castor 125 lock., DIN-PL (gray) (valid from 09/05/2016)	2.0 Each
	<u>382548</u>	Fixed wheel 125 DIN-PL, PA (gray) (valid from 09/05/2016)	2.0 Each
	<u>376812</u>	Corner guard closed RAL7043 (valid from 09/05/2016)	4.0 Each
	<u>376371</u>	Plug corner guard RAL 7043 (valid from 09/05/2016)	16.0 Each
	<u>146680</u>	EXPAND. NUT 72.30.459 F. SHEET SCRW. 4.2 (valid from 09/05/2016)	12.0 Each
	<u>106868</u>	Power switch bipolar 16A B4MASK-series (valid from 09/05/2016)	2.0 Each
	<u>107649</u>	Spiral cable Europe 3x1,5 qmmst WG (valid from 09/05/2016)	1.0 Each
	<u>106304</u>	Cable gland M20x1.5 black (valid from 09/05/2016)	1.0 Each
	<u>106311</u>	Hexagon nut M20x1.5 (plastic) (valid from 09/05/2016)	1.0 Each

Image	Code	Name	Quantity in device
	105429	terminal block Wieland KL 24/3 SL (valid from 12/12/2023)	1.0 Each
	105803	TEMPERATURE LIMITER 115°C (valid from 09/05/2016)	2.0 Each
	369654	Plug holder universal (valid from 09/05/2016)	1.0 Each
	117766	plastic cover ring for plug holder (valid from 10/13/2021)	1.0 Each
	105899	Thermostat capillar 55.18019.130 35-85°C (valid from 09/05/2016)	2.0 Each
	267063	Seal for controller + switch (valid from 09/05/2016)	2.0 Each
	70671	Wiring harness STW 2 capillary tube cont (valid from 09/05/2016)	1.0 Each
	292846	Toggle dia. 42 with labelling (valid from 09/05/2016)	2.0 Each
	298875	Gallery (valid from 09/05/2016)	4.0 Each
	363258	Tube D32x1,5-612 (valid from 09/05/2016)	1.0 Each
	376808	Push-handle holder right RAL7043 (valid from 09/05/2016)	1.0 Each
	376809	Push-handle holder left RAL7043 (valid from 09/05/2016)	1.0 Each

Image	Code	Name	Quantity in device
	<u>81320</u>	Tapping screw ISO7051-ST4,2x19 (valid from 09/05/2016)	4.0 Each
	<u>376810</u>	Cover for rght. push hand., grey RAL7043 (valid from 09/05/2016)	1.0 Each
	<u>376811</u>	Cover for left push hand., grey RAL7043 (valid from 09/05/2016)	1.0 Each
	<u>146497</u>	Glass wool 810x600x20 (valid from 09/05/2016)	1.0 Each
	<u>146498</u>	Glass wool 640x600x20 (valid from 09/05/2016)	2.0 Each
	<u>146514</u>	Glass wool 500x740x20 (valid from 09/05/2016)	1.0 Each
	<u>146507</u>	Glass wool 265x590x20 (valid from 09/05/2016)	3.0 Each