

Sparepart documentation



BPT 420 KBRUH red

Prod. No.: 574576

Product details:

B.PROTHERM 420 KBRUH
Synthetic food transport container, convection-heated;
with hinged door, can be swivelled 270°.
11 pairs of support ledges
Space between ledges: 31 mm
Temperature range adjustable between +40 °C and +95 ° C
Mains frequency: 50/60 Hz

Capacity: 2x GN 1/1-150 or its subdivisions

Basic model: 380904

Spareparts







Image	Code	Name	Quantity in device
	121804	Rep. Set BPT power cord L=2,2m (valid from 09/17/2018)	1.0 Each
	121660	Rep-kit handles for BPT 420/620 K red (valid from 03/20/2017)	2.0 Each
	134030	Rep-Set BPT 420/620 Griff gelasert 2 Stk (valid from 08/20/2019)	1.0 Each
	121715	Rep-kit BPT 160/320/420/620 skids red (valid from 03/20/2017)	1.0 Each
	121709	Rep-kit corners BPT 420/620K red (valid from 03/20/2017)	1.0 Each
	121741	Rep set BPT 420 KB d. cpl. without HM re (valid from 03/20/2017)	1.0 Each
	121700	Rep-Set BPT 620/420 fastener from 7/10 r (valid from 03/20/2017)	1.0 Each

Image	Code	Name	Quantity in device
	<u>121703</u>	Rep-Set BPT 420/620 hinge from 03/13 red (valid from 03/20/2017)	1.0 Each
	<u>121678</u>	Rep-Set 420/620 KBRUH control unit red (valid from 03/20/2017)	1.0 Each
	<u>121796</u>	Rep-Set flap for control unit red (valid from 03/20/2017)	1.0 Each
	<u>121706</u>	rep-kit BPT K plugs red (8 pieces) (valid from 03/20/2017)	1.0 Each
	<u>134290</u>	Conversion kit BPT 420/620 KBRUHE HM red (valid from 02/11/2026)	1.0 Each
	<u>118558</u>	BPT KB(R)UH, radial fan, air duct (valid from 03/20/2017)	1.0 Each
	<u>107012</u>	BPT KB(R)UH radial fan V0 to V4 (valid from 03/20/2017)	1.0 Each
	<u>118731</u>	Rep-Set BPT KB(R)UH fan Heater.-PTC (valid from 03/20/2017)	1.0 Each
	<u>118732</u>	Rep-kit air channel BPT 420/620 KB(R)UH (valid from 03/20/2017)	1.0 Each
	<u>121803</u>	Rep-Set BPT KB(R)UH Electrical housing (valid from 09/17/2018)	1.0 Each
	<u>107014</u>	Repair kit BPT KBRUH NTC sensor 10K (valid from 03/20/2017)	1.0 Each

