

Sparepart documentation



BPT E 30 H

Prod. No.: 575202

Product details:

B.PROTHERM E 30 x 1/1 heated
B.PROTHERM E food transport container 1/1, convection-heated
Made of corrosion-resistant steel, with hinged door, mobile.
30 pairs of support ledges
Space between ledges: 38.3 mm
Temperature range adjustable between +30 °C and +95°C.
Mains frequency: 50/60 Hz
Base model: 386608

Spareparts







Image	Code	Name	Quantity in device
	386752	Mounting bracket (valid from 12/16/2021)	1.0 Each
	386649	Corpus hinge top right (valid from 12/16/2021)	1.0 Each
	374840	Rubber buffer D25xh12-d5 (valid from 12/16/2021)	1.0 Each
	386867	Tube Ø25x1,0 L=586,4 (valid from 12/16/2021)	1.0 Each
	386569	body for push handle holder Ø25 (valid from 12/16/2021)	2.0 Each
	372913	Cover push handle holder left, logo (valid from 12/16/2021)	1.0 Each
	372912	Cover push handle holder right, logo (valid from 12/16/2021)	1.0 Each

Image	Code	Name	Quantity in device
	386652	Hinge (valid from 12/16/2021)	1.0 Each
	83031	washer A 8.4 DIN 125 brass (valid from 12/16/2021)	1.0 Each
	387165	Warm module cpl. 950 W (valid from 01/05/2022)	1.0 Each
	105913	Radial fan R2A 150-AC01-21 (valid from 01/05/2022)	1.0 Each
	107748	Insulating plate (valid from 12/16/2021)	1.0 Each
	107672	Tubular heater 950W 20.43035.010 (valid from 01/05/2022)	1.0 Each
	107694	Temperature sensor PT1000_B. PROTHERM (valid from 01/05/2022)	1.0 Each
	105805	Safety temperature limiter 135 °C (valid from 01/05/2022)	1.0 Each





Image	Code	Name	Quantity in device
	<u>386579</u>	mold without lock <i>(valid from 12/16/2021)</i>	1.0 Each
	<u>386766</u>	Push Rod 30 <i>(valid from 12/16/2021)</i>	1.0 Each
	<u>386771</u>	Spring cpl. <i>(valid from 12/16/2021)</i>	1.0 Each
	<u>386565</u>	Door handle <i>(valid from 12/16/2021)</i>	1.0 Each
	<u>387941</u>	Emergency opening <i>(valid from 03/11/2026)</i>	1.0 Each
	<u>386562</u>	Cover <i>(valid from 12/16/2021)</i>	1.0 Each





















Image	Code	Name	Quantity in device
	389058	Bushing (valid from 12/16/2021)	1.0 Each
	377734	Pressure spring VD-180-07 (valid from 12/16/2021)	1.0 Each
	386778	Seal (valid from 12/16/2021)	3.188 Meter
	389005	Ventilation flap (valid from 08/09/2024)	1.0 Each
	365428	O-RING, 67.00 X 1.50 EPDM70 (valid from 12/16/2021)	1.0 Each
	386580	Retaining tube for ventilation flap (valid from 12/16/2021)	1.0 Each
	107664	BPT Display (valid from 01/05/2022)	1.0 Each
	386547	Display Mount (valid from 01/05/2022)	1.0 Each
	386476	Display Foil Atlas (valid from 01/05/2022)	1.0 Each
	369654	Plug holder universal (valid from 01/05/2022)	1.0 Each
	117766	plastic cover ring for plug holder (valid from 12/16/2021)	1.0 Each

Image	Code	Name	Quantity in device
	<u>105429</u>	terminal block Wieland KL 24/3 SL (valid from 01/05/2022)	1.0 Each
	<u>107722</u>	BPT Power PCB (valid from 01/05/2022)	1.0 Each
	<u>106304</u>	Cable gland M20x1.5 black (valid from 01/05/2022)	1.0 Each
	<u>106311</u>	Hexagon nut M20x1.5 (plastic) (valid from 01/05/2022)	1.0 Each
	<u>106708</u>	magnetic switch MK4-1A75-C-300W (valid from 01/05/2022)	1.0 Each
	<u>107692</u>	Decal equipotential bonding (valid from 01/05/2022)	1.0 Each
	<u>107682</u>	Spiral cable Europe 3x1,5 qmm BL-570 (valid from 01/05/2022)	1.0 Each
	<u>386501</u>	Swivel castor 125 lock., DIN-PL (gray) (valid from 08/24/2022)	2.0 Each
	<u>382548</u>	Fixed wheel 125 DIN-PL, PA (gray) (valid from 12/16/2021)	2.0 Each